



Inspired Concrete... Create **it**. Protect **it**.

INTERIOR CONCRETE FLOORING

PRODUCT SELECTION &
DESIGN INSPIRATION

From new concrete installations to reworking an existing slab, Surecrete overlays can transform utilitarian grey concrete into a custom and functional work of art. The ARTISAN SYSTEM combines compatible products with the expertise of tried and true installation methods.



STEPS AND PROCEDURES



SELECTION OF MATERIALS

With ARTISAN Interior Concrete Flooring systems, YOU get to choose the look.

Our MICROTEK overlay materials produce a **smooth, refined** surface that provides a sophisticated, easy to maintain floor - perfect for both residential and commercial installations. Designers specify these types of systems where a natural, "minimal" finish is desired, with the added benefit of unlimited color options and consistent finish not typically found in "standard" concrete floors.

For a more **rugged, textured, or stone inspired** look, the SURESTAMP overlay system allows for a variety of textures and patterns to be achieved using concrete imprinting tools. A great option for commercial and residential spaces that require not only aesthetic appeal but durability to match.



01 PREP IT. Surface Preparation

SCR Super Concrete Renovator:

Combines three products in one; a strong detergent, degreaser, and acid to ensure proper cleaning and etching for concrete overlays, stains and sealers.*



SCT-22: A rapid setting, ultra low-viscosity urethane spall and crack treatment for concrete.

02 REPAIR IT. Surface Repair

FLASH PATCH: High strength, concrete patching material that is rapid-setting and self-bonding. Patch from feather edge up to 1".



DEEP PATCH: Repairs deep voids in concrete, from 1/8" up to 4" in one lift.*



SUREBOND: Cement-based bonding agent used with Deep Patch and SureStamp as the bond/primer coat.

**Refer to International Concrete Repair Institute Guidelines for surface prep and profile numbers for your specific project, along with SureCrete Technical Data Sheets for each overlay products.*

03 TRANSFORM IT. Cement Based Overlay

MICRO TOPPING - A just add water, self bonding, cement-based overlay system for interior concrete floors. Can be integrally colored, or topically stained with SureCrete's acid or water based stains (see section 04 for details).

Select your product based on floor conditions:



SUREBROOM
Base coat for damaged/uneven surfaces



MICROTEK Smooth Grade:
Finish coat



MICROTEK One Coat:
Standard base coat

SURE STAMP: A stampable, cement-based topping for transforming existing concrete surfaces. At 3/8" thickness, a variety of textures and patterns can be embossed into the material to resemble a wide spectrum of natural stone, wood, tile and brick.



SURESTAMP Must be used with **SURE-BOND** to ensure the ultimate adhesion in a stampable overlay, and **SURERELEASE** for stamping tools and equipment.

Customize colors and enhance visual texture with compatible colors and product (see section 04 for details)

04 ENHANCE IT. Color & Decorate

From subtle to exotic, SureCrete has a wide range of coloring and enhancing materials to personalize your overlay to look perfect no matter what design criteria is desired.

ECO STAIN: 30 semi-transparent water-based concentrate colors. Can be diluted up to 10:1 with water to create a wide range of color intensities. Additionally compatibility to combine colors for an unlimited color palette.



ECO ACCENT: Dry powder concentrate antiquing agent, when mixed with water can be used to enhance visual texture in stamped and textured surfaces.



VIVID Stain: Unlike other coloration methods, VIVID acid stain chemically reacts with the cement-based surface to create a mottled, variegated color that is one-of-a kind. 11 standard colors can be used over both MICROTEK or SURE-STAMP flooring systems.

05 PROTECT IT. Sealers and Finishes

Installing a high-quality protective sealer on your overlay system will not only make it look great, but also protect it from abrasion, wear and staining.

Standard Exposure Environments:

SUPER 20/SUPER 30: 20% or 30% solids, clear, solvent-based acrylic.



Ultra High Performance Environments:

DK 400WB: Water based, 57% solids, dual component polyurethane clear coating. Excellent UV stability, flexibility and chemical and scratch resistance with easy recoat properties. Gloss and satin formulations.

DK 400: Solvent-based, 51% solids, dual component polyurethane clear coating. High gloss, non-yellowing and delivering superb chemical and scratch resistance while enhancing colors.

SUREFINISH: Industrial-grade, sacrificial floor wax. Apply as needed to provide durable floor protection.



ARTISAN SYSTEMS BY SURECRETE & TK PRODUCTS

11400 W 47th Street Minnetonka, MN 55343

P: 800-441-2129 | F: 952-938-8084 | www.surecretedesign.com | www.tkproducts.com