

Features:

- High-Build Sealers Provide Added Protection
- Sacrificial Coats Available
- Masonry Sealers for Natural and Artificial Stone



High-Build and Other Sealers

UV ShieldTM UV-Resistant Epoxy Topcoat

A 100% solids and 100% cross-linked product that can be applied to almost any surface: concrete, wood, tile, stone etc. It is used mainly as a clear coat over full or partial flake or quartz systems, or over VIVIDTM Acid Stains or QuickDyeTM.

Coverage: 100-200ft²/gallon

- Interior Use Only
- Enhances Color
- High Gloss Finish
- Increased Durability

DuraWaxTM Acrylic Floor Wax

This acrylic wax that provides a tough sacrificial coat absorbing wear, making long-term floor maintenance easier. DuraWaxTM is easy to apply and may be re-applied several times without stripping previous applications. This product may be applied on SuperSealTM, PS-18TM, and GemKoteTM sealers as well as ShieldTM epoxies.

Coverage: 1,000-3,000ft²/gallon

- Interior/Exterior Use
- No odor
- Low VOCs
- Quick Drying

SuperGlazeTM WBU Water-Based Urethane

SuperGlazeTM WBU is a single- or dual-component water-based urethane for non-vehicular applications. For dual-component properties, just add QZ-43 Cross-Linker. Has low VOC content with very low odor and quick-drying properties. Requires a primer.

Coverage: 300-400ft²/gallon

- Great Working Time
- Quick Drying
- Excellent Moisture Retention
- Single- or Dual-Component

Dri-LookTM Water-Based Masonry Sealer

Designed specifically for brick and manufactured stone surfaces to provide an invisible barrier against water and the elements, yet leave the natural look of these surfaces with no visible sheen. Micronized polymers provide all the necessary protection to extend the life of these surfaces.

Coverage: About 600ft²/gallon (sprayed)

- Interior/Exterior Use
- Water Resistant
- Invisible Finish
- No Odor or Silicone

Features:

- Add Brilliance and Luster
- Protect Against UV, Fading, Yellowing and Untimely Wear
- 100% Acrylic Resins
- No Fillers



Acrylic Sealer Products

SuperSeal™ 2000 *Solvent-Based 600, 400, 350 and 100 VOC*

Our most popular sealer, SuperSeal™ 2000 is an aromatic acrylic sealer that can be applied to almost any surface - concrete, tile, cementitious overlays and much more. Use SuperSeal™ 2000 for a gloss finish as well as for its UV and stain protection.

Coverage: 150-200ft²/gallon

- Interior/Exterior Use
- Gloss "Wet Look" Finish
- Enhances Color
- Also available in Matte

GemKote™ *Solvent-Based 400, 350 and 100 VOC*

GemKote™ sealers use the same resin as SuperSeal™ 2000, but offer VOC contents less than 400g/l, 350g/l or 100g/l for local regulations requiring lower VOCs. GemKote™ is an aromatic acrylic sealer that can be applied to almost any surface - concrete, tile, cementitious overlays and much more. Use GemKote™ for a gloss finish as well as for its UV and stain protection.

Coverage: 150-200ft²/gallon

- Interior/Exterior Use
- Gloss "Wet Look" Finish
- Enhances Color
- Also available in Matte

Caution: May Be Flammable

Before using or handling, read the Material Safety Data Sheets, Technical Data Sheets and Warranty. DO NOT TAKE INTERNALLY! Avoid contact with skin and eyes. Use only with adequate ventilation and use a respirator when levels are above application limits. Check local regulations for VOC requirements.

PS-18™ *Solvent-Based 600, 400, 350 and 100 VOC*

PS-18™ is a non-yellowing acrylic solvent-based sealer that aids in the curing process of freshly-placed concrete. Traditional curing and sealing agents are usually meant as a sacrificial coat and are often required to be removed before applying a finish sealer. PS-18™ contains the same resin as SuperSeal™ 2000 and GemKote™ sealers, thereby allowing complete compatibility with these sealers. Use PS-18™ for a gloss finish as well as for its UV and stain protection.

Coverage: 150-200ft²/gallon

- Interior/Exterior Use
- Excellent Moisture Retention
- Enhances Color
- Available in Gloss and Matte

SuperSeal™ 20WB *Water-Based Low VOC*

With a VOC content less than 90g/l, this everyday, general use water-based sealer is a green alternative that may be used when a solvent-based product cannot due to safety or flammability concerns. Can be applied to almost any surface - concrete, tile, cementitious overlays and much more. Use SuperSeal™ 20WB for a matte finish and for its low VOCs and weatherability.

Coverage: 300-400ft²/gallon

- Interior/Exterior Use
- Low VOCs
- No odor
- Quick Drying